



Research & Development

PRODUCT DATA SHEET

YASAKI 2-STROKE OUTBOARD M.O

API TC SAE 30

PRODUCT DESCRIPTION

YASAKI 2-STROKE Outboard Motor Oil is a superior quality, non-ash forming SAE 30 two stroke motor oil. It is dyed blue for ease of use and identification. 2T provides miscibility and fluidity characteristics that meet grade 2 of SAE J 1536 and exceeds the API TC performance level.

PERFORMANCE LEVEL

API TC, SAE J1536 GRADE 2, JASO FC

BENEFITS AND ADVANTAGES:

- Effective lubrication at varying speeds
- Longer spark plug life
- Maintains optimum viscosity at different temperatures
- Meets and exceeds API TC

SPECIFICATION & TECHNICAL PARAMETER

SL #	SAE VISOSITY GRADE 30		
1.	Color	D 1500	Blue
2.	Kin. Viscosity @ 100 °C	D 445	10.76
3.	Kin. Viscosity @ 40 °C	D 445	76
4.	Density @ 60/60F	D 1298	0.878
5.	Viscosity Index	D 2270	107
6.	Pour Point	D 97	≤-30
7.	Flash Point	D 92	≥180
8.	Water Content	Crackle	-ve
9.	Foam Seq I, II, III	D 892	PASS

*Technical data provided here is for reference only. Minor variations in product typical test data are to be expected. **All the information contained in this document is considered to be accurate as of the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy of the data and information in this publication. It is the user's obligations to evaluate and use the products safely and to comply with all applicable laws and regulations. For more information, please contact your sales representative.